

Technical parameters							
Model (s):	ACHP-H08/4R3HA-ME ACHP-H08/4R3HA-M (NE)						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Warmer						
Declared temperature application	Low						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	8.1	kW	Seasonal space heating energy efficiency	η_s	173	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	-	kW	Tj = -7°C	COPd	-	-
Tj = +2°C	Pdh	8.10	kW	Tj = +2°C	COPd	2.62	-
Tj = +7°C	Pdh	5.21	kW	Tj = +7°C	COPd	3.78	-
Tj = +12°C	Pdh	2.31	kW	Tj = +12°C	COPd	5.55	-
Tj = bivalent temperature	Pdh	5.21	kW	Tj = bivalent temperature	COPd	3.78	-
Tj = operation limit temperature	Pdh	8.10	kW	Tj = operation limit temperature	COPd	2.62	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj=-15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	Peych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0.020	kW	Rated heat output (*)	Psup	0.3	kW
Thermostat-off mode	P _{TO}	0.030	kW	Type of energy input	Electricity		
Standby mode	P _{SB}	0.020	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4000	m ³ /h
Sound power level	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	QHE	2460	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	Hwh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh =0.9							

Technical parameters							
Model(s):		ACHP-H08/4R3HA-ME ACHP-H08/4R3HA-M (NE)					
Air-to-water heat ump:		yes					
Water-to-water heat pump:		no					
Brine-to-water heat pump:		no					
Low-temperature heat pump:		no					
Equipped with a supplementary heater:		no					
Heat pump combination heater:		no					
Declared climate condition		Warmer					
Declared temperature application		Medium					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	7.6	kW	Seasonal space heating energy efficiency	η_s	173	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	-	kW	Tj = -7°C	COPd	-	-
Tj = +2°C	Pdh	7.30	kW	Tj = +2°C	COPd	2.59	-
Tj = +7°C	Pdh	4.89	kW	Tj = +7°C	COPd	3.90	-
Tj = +12°C	Pdh	2.17	kW	Tj = +12°C	COPd	5.55	-
Tj = bivalent temperature	Pdh	4.89	kW	Tj = bivalent temperature	COPd	3.92	-
Tj = operation limit temperature	Pdh	7.30	kW	Tj = operation limit temperature	COPd	2.59	-
For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	P _{psych}	-	kW	Cycling interval efficiency	COP _{cyc}	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	0.0	kW
Thermostat-off mode	P _{TO}	0.030	kW				
Standby mode	P _{SB}	0.020	kW				
Crankcase heater mode	P _{cK}	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4000	m ³ /h
Sound power level	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	QHE	2304	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	Q _{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9							

Technical parameters										
Model(s):	ACHP-H08/4R3HA-ME ACHP-H08/4R3HA-M (NE)									
Air-to-water heat ump:	yes									
Water-to-water heat pump:	no									
Brine-to-water heat pump:	no									
Low-temperature heat pump:	no									
Equipped with a supplementary heater:	no									
Heat pump combination heater:	no									
Declared climate condition	Average									
Declared temperature application	Low									
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit			
Rated heat output(*)	Prated	8.1	kW	Seasonal space heating energy efficiency	η_s	205	%			
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj						
Tj = -7°C	Pdh	7.18	kW	Tj = -7°C	COPd	3.30	-			
Tj = +2°C	Pdh	4.36	kW	Tj = +2°C	COPd	5.09	-			
Tj = +7°C	Pdh	2.80	kW	Tj = +7°C	COPd	6.82	-			
Tj = +12°C	Pdh	1.25	kW	Tj = +12°C	COPd	8.35	-			
Tj = bivalent temperature	Pdh	7.18	kW	Tj = bivalent temperature	COPd	3.30	-			
Tj = operation limit temperature	Pdh	6.44	kW	Tj = operation limit temperature	COPd	3.04	-			
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-			
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C			
Cycling interval capacity for heating	P _{psych}	-	kW	Cycling interval efficiency	COP _{psych}	-	-			
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C			
Power consumption in modes other than active mode				Supplementary heater						
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	1.66	kW			
Thermostat-off mode	P _{TQ}	0.030	kW							
Standby mode	P _{SB}	0.020	kW					Type of energy input	Electricity	
Crankcase heater mode	P _{cK}	0.000	kW							
Other items										
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4000	m ³ /h			
Sound power level	LWA	-	dB	For water/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h			
Annual energy consumption	QHE	3216	kWh							
For heat pump combination heater										
Declared load profile	-			Water heating energy efficiency	O _{wh}	-	%			
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh			
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China									
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9										

Technical parameters							
Model(s):	ACHP-H08/4R3HA-ME ACHP-H08/4R3HA-M (NE)						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Average						
Declared temperature application	Medium						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	6.6	kW	Seasonal space heating energy efficiency	η_s	132	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	5.84	kW	Tj = -7°C	COPd	2.30	-
Tj = +2°C	Pdh	3.55	kW	Tj = +2°C	COPd	3.30	-
Tj = +7°C	Pdh	2.28	kW	Tj = +7°C	COPd	4.28	-
Tj = +12°C	Pdh	1.02	kW	Tj = +12°C	COPd	5.33	-
Tj = bivalent temperature	Pdh	5.84	kW	Tj = bivalent temperature	COPd	2.16	-
Tj = operation limit temperature	Pdh	4.90	kW	Tj = operation limit temperature	COPd	1.84	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Ppsych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P OFF	0.020	kW	Rated heat output (*)	Psup	1.7	kW
Thermostat-off mode	PTO	0.030	kW	Type of energy input	Electricity		
Standby mode	P SB	0.020	kW				
Crankcase heater mode	PcK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4000	m ³ /h
Sound power level	LWA	59	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	QHE	4015	kWh				
For heat pump combination heater							
Declared load profile	-			Water heating energy efficiency	Owh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
<p>(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).</p> <p>(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9</p>							

Technical parameters							
Model(s):	ACHP-H08/4R3HA-ME ACHP-H08/4R3HA-M (NE)						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Colder						
Declared temperature application	Low						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	7.0	kW	Seasonal space heating energy efficiency	η_s	168	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	4.46	kW	Tj = -7°C	COPd	3.66	-
Tj = +2°C	Pdh	2.69	kW	Tj = +2°C	COPd	5.20	-
Tj = +7°C	Pdh	1.65	kW	Tj = +7°C	COPd	6.53	-
Tj = +12°C	Pdh	1.65	kW	Tj = +12°C	COPd	7.96	-
Tj = bivalent temperature	Pdh	5.69	kW	Tj = bivalent temperature	COPd	2.83	-
Tj = operation limit temperature	Pdh	4.06	kW	Tj = operation limit temperature	COPd	1.95	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Ppsych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	52	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P OFF	0.020	kW	Rated heat output (*)	Psup	2.94	kW
Thermostat-off mode	PTO	0.030	kW	Type of energy input	Electricity		
Standby mode	P SB	0.020	kW				
Crankcase heater mode	PcK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4000	m ³ /h
Sound power level	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	QHE	4036	kWh				
For heat pump combination heater							
Declared load profile	-			Water heating energy efficiency	Owh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
<p>(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).</p> <p>(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9</p>							

Technical parameters							
Model(s):	ACHP-H08/4R3HA-ME ACHP-H08/4R3HA-M (NE)						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Colder						
Declared temperature application	Medium						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	5.8	kW	Seasonal space heating energy efficiency	η_s	111	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	3.86	kW	Tj = -7°C	COPd	2.48	-
Tj = +2°C	Pdh	2.21	kW	Tj = +2°C	COPd	3.35	-
Tj = +7°C	Pdh	1.44	kW	Tj = +7°C	COPd	4.11	-
Tj = +12°C	Pdh	1.47	kW	Tj = +12°C	COPd	5.92	-
Tj = bivalent temperature	Pdh	4.71	kW	Tj = bivalent temperature	COPd	1.90	-
Tj = operation limit temperature	Pdh	2.80	kW	Tj = operation limit temperature	COPd	1.22	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Ppsych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	52	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P OFF	0.020	kW	Rated heat output (*)	Psup	3.0	kW
Thermostat-off mode	P TO	0.030	kW	Type of energy input	Electricity		
Standby mode	P SB	0.020	kW				
Crankcase heater mode	P cK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4000	m ³ /h
Sound power level	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	QHE	5014	kWh				
For heat pump combination heater							
Declared load profile	-			Water heating energy efficiency	Owh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
<p>(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).</p> <p>(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9</p>							