

Technical parameters							
Model(s):	ACHP-H14/4R3HA-ME ACHP-H14/4R3HA-M(NE) ACHP-H14/5R3HA-M						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Warmer						
Declared temperature application	Low						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	12.1	kW	Seasonal space heating energy efficiency	η_s	259	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	-	kW	Tj = -7°C	COPd	-	-
Tj = +2°C	Pdh	12.00	kW	Tj = +2°C	COPd	3.44	-
Tj = +7°C	Pdh	7.78	kW	Tj = +7°C	COPd	5.84	-
Tj = +12°C	Pdh	3.75	kW	Tj = +12°C	COPd	8.25	-
Tj = bivalent temperature	Pdh	7.78	kW	Tj = bivalent temperature	COPd	5.84	-
Tj = operation limit temperature	Pdh	12.00	kW	Tj = operation limit temperature	COPd	3.44	-
For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	P _{ych}	-	kW	Cycling interval efficiency	COP _{cyc}	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	0.10	kW
Thermostat-off mode	P _{TO}	0.030	kW	Type of energy input	Electricity		
Standby mode	P _{SB}	0.020	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated airflow rate, outdoors	-	4650	m ³ /h
Sound power levelL	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	Q _{HE}	2463	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	H _{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
<p>(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).</p> <p>(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9</p>							

Technical parameters							
Model(s):	ACHP-H14/4R3HA-ME ACHP-H14/4R3HA-M(NE) ACHP-H14/5R3HA-M						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Warmer						
Declared temperature application	Medium						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	14.1	kW	Seasonal space heating energy efficiency	η_s	175	%
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	-	kW	Tj = -7°C	COPd	-	-
Tj = +2°C	Pdh	14.0	kW	Tj = +2°C	COPd	2.42	-
Tj = +7°C	Pdh	9.06	kW	Tj = +7°C	COPd	3.53	-
Tj = +12°C	Pdh	4.03	kW	Tj = +12°C	COPd	6.16	-
Tj = bivalent temperature	Pdh	9.06	kW	Tj = bivalent temperature	COPd	3.53	-
Tj = operation limit temperature	Pdh	14.00	kW	Tj = operation limit temperature	COPd	2.42	-
For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (if TOL < -20°C)	COPd	-	-
Bivalent temperature	Tbiv	7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	P _{psych}	-	kW	Cycling interval efficiency	COP _{psych}	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{OFF}	0.020	kW	Rated heat output (*)	P _{sup}	0.10	kW
Thermostat-off mode	P _{TO}	0.030	kW	Type of energy input	Electricity		
Standby mode	P _{SB}	0.020	kW				
Crankcase heater mode	P _{CK}	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated airflow rate, outdoors	-	4650	m ³ /h
Sound power level	LWA	-	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	Q _{HE}	4235	kWh				
For heat pump combination heater							
Declared load profile	-			Water heating energy efficiency	H _{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0.9							

Technical parameters							
Model(s):	ACHP-H14/4R3HA-ME ACHP-H14/4R3HA-M (NE) ACHP-H14/5R3HA-M						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Average						
Declared temperature application	Low						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	14.5	kW	Seasonal space heating energy efficiency	η_s	188	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	12.83	kW	Tj = -7°C	COPd	3.00	-
Tj = +2°C	Pdh	7.81	kW	Tj = +2°C	COPd	4.74	-
Tj = +7°C	Pdh	5.02	kW	Tj = +7°C	COPd	5.82	-
Tj = +12°C	Pdh	2.23	kW	Tj = +12°C	COPd	9.20	-
Tj = bivalent temperature	Pdh	12.83	kW	Tj = bivalent temperature	COPd	3.00	-
Tj = operation limit temperature	Pdh	11.46	kW	Tj = operation limit temperature	COPd	2.73	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Peych	-	kW	Cycling interval efficiency	COPeyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0.020	kW	Rated heat output (*)	Psup	3.4	kW
Thermostat-off mode	P TQ	0.030	kW	Type of energy input	Electricity		
Standby mode	^s SB	0.020	kW				
Crankcase heater mode	PcK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m ³ /h
Sound power level	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	QHE	6257	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	Hwh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).							
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh =0.9							

Technical parameters							
Model(s):	ACHP-H14/4R3HA-ME ACHP-H14/4R3HA-M(NE) ACHP-H14/5R3HA-M						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Average						
Declared temperature application	Medium						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	14	kW	Seasonal space heating energy efficiency	η_s	137	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	12.38	kW	Tj = -7°C	COPd	2.06	-
Tj = +2°C	Pdh	7.54	kW	Tj = +2°C	COPd	3.50	-
Tj = +7°C	Pdh	4.85	kW	Tj = +7°C	COPd	4.33	-
Tj = +12°C	Pdh	2.15	kW	Tj = +12°C	COPd	6.97	-
Tj = bivalent temperature	Pdh	12.38	kW	Tj = bivalent temperature	COPd	2.06	-
Tj = operation limit temperature	Pdh	10.50	kW	Tj = operation limit temperature	COPd	1.80	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Psych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0.020	kW	Rated heat output (*)	Psup	3.5	kW
Thermostat-off mode	PTO	0.030	kW	Type of energy input	Electricity		
Standby mode	PSB	0.020	kW				
Crankcase heater mode	PCK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m³/h
Sound power levelL	LWA	64	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	8251	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	Qwh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh =0.9							

Technical parameters							
Model ⑥:	ACHP-H14/4R3HA-ME ACHP-H14/4R3HA-M(NE) ACHP-H14/5R3HA-M						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Colder						
Declared temperature application	Low						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	12.6	kW	Seasonal space heating energy efficiency	η_s	159	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	7.96	kW	Tj = -7°C	COPd	3.44	-
Tj = +2°C	Pdh	5.05	kW	Tj = +2°C	COPd	4.92	-
Tj = +7°C	Pdh	3.15	kW	Tj = +7°C	COPd	6.11	-
Tj = +12°C	Pdh	3.57	kW	Tj = +12°C	COPd	7.82	-
Tj = bivalent temperature	Pdh	10.31	kW	Tj = bivalent temperature	COPd	2.53	-
Tj = operation limit temperature	Pdh	7.57	kW	Tj = operation limit temperature	COPd	1.92	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C (ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Peych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	52	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0.020	kW	Rated heat output (*)	Psup	5.03	kW
Thermostat-off mode	PTO	0.030	kW				
Standby mode	PSB	0.020	kW				
Crankcase heater mode	PCK	0.000	kW				
Type of energy input							
Electricity							
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m ³ /h
Sound power level	LWA	-	dB	For water-to-brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
Annual energy consumption	QHE	7685	kWh				
For heat pump combination heater							
Declared load profile	-			Water heating energy efficiency	Qwh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).							
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh =0.9							

Technical parameters							
Model(s):	ACHP-H14/4R3HA-ME ACHP-H14/4R3HA-M(NE) ACHP-H14/5R3HA-M						
Air-to-water heat ump:	yes						
Water-to-water heat pump:	no						
Brine-to-water heat pump:	no						
Low-temperature heat pump:	no						
Equipped with a supplementary heater:	no						
Heat pump combination heater:	no						
Declared climate condition	Colder						
Declared temperature application	Medium						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output(*)	Prated	11.0	kW	Seasonal space heating energy efficiency	η_s	118	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	6.89	kW	Tj = -7°C	COPd	2.66	-
Tj = +2°C	Pdh	4.32	kW	Tj = +2°C	COPd	3.66	-
Tj = +7°C	Pdh	3.06	kW	Tj = +7°C	COPd	4.72	-
Tj = +12°C	Pdh	3.33	kW	Tj = +12°C	COPd	6.25	-
Tj = bivalent temperature	Pdh	8.94	kW	Tj = bivalent temperature	COPd	1.79	-
Tj = operation limit temperature	Pdh	4.20	kW	Tj = operation limit temperature	COPd	1.13	-
For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C(ifTOL<-20°C)	COPd	-	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Psych	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient(**)	Cdh	0.9	-	Heating water operating limit temperature	WTOL	52	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0.020	kW	Rated heat output (*)	Psup	6.80	kW
Thermostat-off mode	PTO	0.030	kW	Type of energy input	Electricity		
Standby mode	PSB	0.020	kW				
Crankcase heater mode	PCK	0.000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m³/h
Sound power levelL	LWA	-	dB	For water-/brine-to-water heat pumps:Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	8937	kWh				
For heat pump combination heater							
Declaed load profile	-			Water heating energy efficiency	Qwh	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Contact details	AUX Co., Ltd 1166 Mingguang North Road, Jiangshan Yinzhou District, Ningbo, 315191 Zhejiang, China						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh =0.9							